

Product

# STARTEX TAPE

**BUTYL RUBBER COATED NON-WOVEN WITH RELEASE LINER WITH OVERLAPS FOR EASY REMOVAL.**

Characteristics

- **Good cementability good cementability with common tile adhesives or sealants, structure embossing.**
- **Suitable for indoor application**
- **Easy to use**
- **High chemical resistance.**

Application field

Joint sealing tape to be applied with tiles or natural stones for flexible waterproofing of expansion joints. Suitable for indoor application for medium loads of non-pressurized water (e.g. domestic bathrooms).

Application

Remove the release liner, place the corner and press on firmly.

Cut the joint sealing tape to the appropriate wall size before processing. It is essential to plan an overlap of 50 mm to the sealing corner. For a safe overlap of the sealing corner and joint sealing tape you should apply a suitable liquid sealing adhesive. The remaining tapes are processed according to this scheme. Afterwards you can continue with the surface sealing.

technical data

<b>Color</b>	Grey
<b>Resistance to temperature: min. / max.</b>	- 30 °C / + 60 °C
<b>Total width (with release)</b>	80 mm
<b>Product thickness (without release)</b>	0,77 mm
<b>Product weight (without release)</b>	730 g/m <sup>2</sup>
<b>Length per roll</b>	10 m
<b>Breaking load longitudinal DIN EN ISO 527-3</b>	30 N/15 mm
<b>Breaking load lateral DIN EN ISO 527-3</b>	19 N / 15 mm
<b>Extension break longitudinal DIN EN ISO 527-3</b>	60%
<b>Extension break lateral DIN EN ISO 527-3</b>	80%
<b>Resistance to water pressure DIN EN 1928 (Version B)</b>	> 0,2 bar
<b>Peel test on neutral PVC carrier</b>	≥ 13 N / 20 mm
<b>Burst pressure max.max.</b>	0,4 bar

<b>Storage</b>	Cool and dry, protect against sunlight, use within 12 months after receipt
----------------	--

The data and prescriptions contained in this schedule, based on the best practical and laboratory experiences, are to be considered in any case indicative. Given the different conditions of use, and the intervention of factors independent of MPM (support, environmental conditions, technical direction of application, etc.) those intending to use the product are held to establish whether it is suitable or not for the intended use. Our guarantee extends only to the quality and consistency of the finished product with the data given above, and only for technical schedules bearing the stamp and counter signature of the personnel delegated by our offices. The customer is further held to verify that these values are valid for the product batch concerning him and have not be updated and/or substituted by subsequent issues and/or new formulations. The data contained may vary at any moment without any obligation on the part of MPM to give prior notice